

Technical Specifications

DynaPower TD Plus SAE 15W-40

Universal SHPD motor oil for long oil-drain intervals in LCV- and truck diesel engines

DynaPower TD Plus SAE 15W-40 is a high-performance, universal fuel oil for the maintenance of mixed vehicles throughout the year. A uniform engine oil for all vehicles excludes confusion and guarantees economic storage.

DynaPower TD Plus SAE 15W-40 is a powerful universal engine oil for extended oil change intervals.

The performance spectrum covers both the requirements of commercial vehicle and passenger car diesel engines as well as those of petrol engines.

The high requirements of modern, low-consumption engines to meet the more stringent exhaust gas standards (Euro III) are met with reserve.

Technical Data

Viscosity at + 100 °C	14,50 mm ² /s	DIN 51562
Viscosityindex	148	DIN ISO 2909
Density at + 15 °C	0,870 g/cm ³	DIN 51757
Pour point	- 33 °C	DIN ISO 3016
Flash point	> +200 °C	DIN ISO 2592
Base Number BN	9,0 mg KOH/g	DIN ISO 3771

(The physical data are average values)

Classifications

- ACEA A2
- ACEA A3
- ACEA B3
- ACEA E7
- API CI-4
- API SL
- Global DHD-1

Standard application

Caterpillar ECF-1a
Caterpillar ECF-2
Cummins CES 20071
Cummins CES 20072
Cummins CES 20076
Cummins CES 20077
DEUTZ DQC III-10

John Deere JDQ 78 A
Mack EO-N
Mack EO-N Premium Plus 03
MAN M 3275-1 (obsolete)
Mercedes-Benz: MB 228.3
Mercedes-Benz: MB 229.1
MTU DDC BR 2000

MTU DDC BR 4000
MTU Ölkategorie 2
Renault RLD
Renault RLD/RLD-2
Scania LDF
Volvo VDS-3 (STD 417-0002)
ZF TE-ML 07C